

Issue Date 04-Jan-2016

Revision Date: 04-Oct-2017

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Max Hold Sport

### Other means of identification

**SDS #** WTC-005

**UN/ID No** UN1219

### Recommended use of the chemical and restrictions on use

**Recommended Use** Scalp protector.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Walker Tape Co., Inc  
 9312 S. Prosperity Road  
 West Jordan, Utah 84081

### Emergency Telephone Number

**Company Phone Number** Phone: (801) 282-2015  
 Fax: (801) 282-2131  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
 1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

### Classification

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

### Signal Word

**Danger**

### Hazard Statements

Causes serious eye irritation  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Highly flammable liquid and vapor



**Appearance** Clear, colorless liquid

**Physical State** Liquid

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Immediately call a POISON CENTER or doctor/physician  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or alcohol resistant foam to extinguish.

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards Not Otherwise Classified (HNOC)**

May be harmful if swallowed

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Isopropyl Alcohol	67-63-0	80-100
Ethyl-Methacrylate Copolymer	90651-52-8	<20

### 4. FIRST-AID MEASURES

**First Aid Measures**

<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician immediately.
<b>Skin Contact</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, give artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

**Most important symptoms and effects**

**Symptoms** Causes serious eye irritation. May cause mild skin irritation. May cause respiratory irritation. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion or loss of coordination. Headache.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Water spray (fog). Alcohol foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Flammable.

**Hazardous Combustion Products** No information available.

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool containers to prevent pressure build up. Use water spray to disperse vapors - re-ignition is possible.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Use personal protection recommended in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep people away from and upwind of spill/leak.

**Environmental Precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13, Disposal Considerations, for additional information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Clean-Up** Keep in suitable, closed containers for disposal. If fire potential exists, blanket spill with alcohol-type aqueous film-forming foam or use water spray to disperse vapors. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. US regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800)-424-8802.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Do not cut, drill, grind, or weld on or near this container; residual vapors may ignite.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from ignition sources and incompatible materials. Keep cool. Store locked up.

#### **Packaging Materials**

Empty containers retain product residue and can be hazardous.

#### **Incompatible Materials**

Strong oxidizing agents. Amines. Alkanolamines. Aldehydes. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>

### Appropriate engineering controls

#### **Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Eyewash stations. Showers.

### Individual protection measures, such as personal protective equipment

#### **Eye/Face Protection**

Chemical anti-splash safety goggles.

#### **Skin and Body Protection**

Chemical resistant protective gloves. Suitable protective clothing.

#### **Respiratory Protection**

In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.

#### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### **Physical State**

Liquid

#### **Appearance**

Clear, colorless liquid

#### **Odor**

Not determined

#### **Color**

Clear Colorless

#### **Odor Threshold**

Not determined

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	-88 °C / -127 °F	
Boiling Point/Boiling Range	82 °C / 180 °F	
Flash Point	11 °C / 53 °F	Tag Closed Cup
Evaporation Rate	1.4	(butyl acetate = 1)
Flammability (Solid, Gas)	Liquid-not applicable	
Upper Flammability Limits	12%	
Lower Flammability Limit	2%	
Vapor Pressure	32 mmHg	@ 25°C (77°F)
Vapor Density	2.1	(Air=1)
Specific Gravity	0.789	@ 60°F
Water Solubility	Completely soluble	@ 20°C (68°F)
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**      Hazardous polymerization does not occur.

### Conditions to Avoid

Keep out of reach of children.

### Incompatible Materials

Strong oxidizing agents. Amines. Alkanolamines. Aldehydes. Chlorinated compounds.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin Contact</b>	Avoid contact with skin.
<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Ingestion</b>	May be harmful if swallowed.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl Alcohol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h

**Information on physical, chemical and toxicological effects**

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Isopropyl Alcohol (IPA) is listed as an IARC Monograph Group 3 chemical. However, IARC Group 3 chemicals are "not classifiable as human carcinogens". IPA is classified as an IARC Group 1 chemical ONLY when manufactured by the strong-acid process. The IPA used in this product is NOT manufactured by the strong-acid process and is therefore not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl Alcohol 67-63-0		Group 1 Group 3		X

*IARC (International Agency for Research on Cancer)*

*Group 3 IARC components are "not classifiable as human carcinogens"*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropyl Alcohol 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50		13299: 48 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined

**Bioaccumulation**

Not determined

**Mobility**

Chemical Name	Partition Coefficient
Isopropyl Alcohol 67-63-0	0.05

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**                      Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**              Disposal should be in accordance with applicable regional, national and local laws and regulations.

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Isopropyl Alcohol 67-63-0	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**Note**    Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

**UN/ID No**    UN1219  
**Proper Shipping Name**                      Isopropyl alcohol solution  
**Hazard Class**    3  
**Packing Group**    II

**IATA**

**UN/ID No**    UN1219  
**Proper Shipping Name**                      Isopropyl alcohol solution  
**Hazard Class**    3  
**Packing Group**    II

**IMDG**

**UN/ID No**    UN1219  
**Proper Shipping Name**                      Isopropyl alcohol solution  
**Hazard Class**    3  
**Packing Group**    II





