

Issue Date 01-Feb-2012

Revision Date: 04-Oct-2017

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Ultra Hold Adhesive

### Other means of identification

**SDS #** WTC-001

**UN/ID No** UN1133

### Recommended use of the chemical and restrictions on use

**Recommended Use** Liquid Adhesive.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Walker Tape Co., Inc  
 9312 S. Prosperity Road  
 West Jordan, Utah 84081

### Emergency Telephone Number

**Company Phone Number** Phone: (801) 282-2015  
 Fax: (801) 282-2131  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
 1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Signal Word

**Danger**

### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Highly flammable liquid and vapor



**Appearance** Clear viscous liquid

**Physical State** Liquid

**Odor** Characteristic Hydrocarbon Ester

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear eye/face protection  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Get medical attention if irritation occurs  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do not induce vomiting  
 IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
Other Inert Ingredients	Proprietary	<50
Isopropanol	67-63-0	15-25
Ethyl acetate	141-78-6	15-25
N-Heptane	142-82-5	10-20
Toluene	108-88-3	<5

## 4. FIRST-AID MEASURES

### First Aid Measures

<b>General Advice</b>	If exposed or concerned: Get medical advice/attention.
<b>Eye Contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.
<b>Skin Contact</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/ attention.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician.
<b>Ingestion</b>	IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting. If conscious, give 1 glass of water or milk to dilute. Have patient lie down and keep warm. Call a physician.

### Most important symptoms and effects

<b>Symptoms</b>	Causes serious eye irritation. Repeated, frequent or prolonged contact with skin may cause defatting of the skin which can lead to irritation, defatting and/or dermatitis. Overexposure by inhalation may be irritating to respiratory passages and cause other effects such as nausea, dizziness and drowsiness. Irritating to mouth, throat, and stomach if ingested. May cause gastric tract disorder and/or damage. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting, may cause bronchopneumonia or pulmonary edema.
-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO<sub>2</sub>). Foam. Water spray (fog). Use water spray to cool fire-exposed equipment and containers and to disperse vapors.

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Extremely flammable. Vapors are heavier than air and may travel along ground to ignition sources and flash back.

**Hazardous Combustion Products** Combustion may release noxious or toxic vapors.

**Sensitivity to Mechanical Impact** Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite/explode.

**Sensitivity to Static Discharge** May be ignited by friction, heat, sparks or flames. Take precautionary measures against static discharge. Flammable mixtures of this product are readily ignited even by static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Isolate hazard area. Keep unnecessary and unprotected personnel from entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use personal protection recommended in Section 8.
<b>Other Information</b>	For safety and environmental precautions please review entire Safety Data Sheet for necessary information.
<b>Environmental Precautions</b>	See Section 12 for additional Ecological Information. See Section 13, Disposal Considerations, for additional information.

### Methods and material for containment and cleaning up

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Clean-Up</b>	For small spills, absorb with sand, clay, or other inert absorbent. For large spills, dike far ahead of spill for later disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Advice on Safe Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash face, hands, and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Wear eye/face protection. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.
--------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Conditions for safe storage, including any incompatibilities

<b>Storage Conditions</b>	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from ignition sources and incompatible materials. Use only explosion-proof exhaust ventilation. Keep cool. Store at room temperature. Store locked up.
<b>Packaging Materials</b>	Empty containers retain product residue and can be hazardous. See Section 13, Disposal Considerations, for additional information.
<b>Incompatible Materials</b>	Strong oxidizers. Strong acids. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>

N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Explosion-proof general and local exhaust ventilation. Eyewash stations. Showers.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Chemical anti-splash safety goggles.

**Skin and Body Protection** Rubber, neoprene, or other impervious gloves are recommended to prevent skin contact. Suitable protective clothing.

**Respiratory Protection** None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Respiratory protection must be provided in accordance with OSHA regulations (29 CFR1910.134) or European Standard EN 149, as applicable.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke while using this product. Wash hands before eating, drinking, smoking or going to the toilet. Take off all contaminated clothing and wash before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Odor</b>	Characteristic
<b>Appearance</b>	Clear viscous liquid	<b>Odor Threshold</b>	Hydrocarbon Ester No information available
<b>Color</b>	Clear		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>	
pH	Not available		
Melting Point/Freezing Point	Not available		
Boiling Point/Boiling Range	65.5 °C / 150 °F		
Flash Point	< -6.6 °C / < 20 °F	(Seta Closed Cup)	
Evaporation Rate	> 1	(butyl acetate = 1)	
Flammability (Solid, Gas)	Liquid-not applicable		
Upper Flammability Limits	13.0		
Lower Flammability Limit	1.3		
Vapor Pressure	180 mmHg	@ 20 C	
Vapor Density	~3	(Air=1)	
Specific Gravity	0.840	(1=Water)	
Water Solubility	Slightly soluble		
Solubility in other solvents	Not determined		
Partition Coefficient	Some partitioning		See Section 12 for additional Ecological Information
Autoignition Temperature	Not available		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		

<b>Explosive Properties</b>	May form explosive mixtures with air
<b>Oxidizing Properties</b>	Not Applicable
<b>VOC Content</b>	3.85 lb/gal (462 g/l)
<b>Bulk Density</b>	7.0 lb/gal

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization** No information available.

### Conditions to Avoid

Keep out of reach of children.

### Incompatible Materials

Strong oxidizers. Strong acids. Strong bases.

### Hazardous Decomposition Products

Thermal decomposition may yield oxides of carbon. Volatile organic compounds.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin Contact</b>	Causes skin irritation.
<b>Inhalation</b>	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Other Inert Ingredients	> 90 mL/kg ( Rat )	-	-
Isopropanol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h
Ethyl acetate 141-78-6	= 5620 mg/kg ( Rat )	> 20 mL/kg ( Rabbit ) > 18000 mg/kg ( Rabbit )	-
N-Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h
Toluene 108-88-3	= 636 mg/kg ( Rat )	= 8390 mg/kg ( Rabbit ) = 12124 mg/kg ( Rat )	= 12.5 mg/L ( Rat ) 4 h > 26700 ppm ( Rat ) 1 h

### Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Isopropyl Alcohol (IPA) is listed as an IARC Monograph Group 3 chemical. However, IARC Group 3 chemicals are "not classifiable as human carcinogens". IPA is classified as an IARC Group 1 chemical ONLY when manufactured by the strong-acid process. The IPA used in this product is NOT manufactured by the strong-acid process and is therefore not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0		Group 1 Group 3		X
Toluene 108-88-3		Group 3		

**IARC (International Agency for Research on Cancer)**

Group 3 IARC components are "not classifiable as human carcinogens"

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT - single exposure**

May cause damage to organs. May cause respiratory irritation.

**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropanol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50		13299: 48 h <i>Daphnia magna</i> mg/L EC50
Ethyl acetate 141-78-6	3300: 48 h <i>Desmodesmus subspicatus</i> mg/L EC50	220 - 250: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 484: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 352 - 500: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	560: 48 h <i>Daphnia magna</i> mg/L EC50 Static
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50		10: 24 h <i>Daphnia magna</i> mg/L EC50

<p>Toluene 108-88-3</p>	<p>433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static</p>	<p>15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static</p>	<p>EC50 = 19.7 mg/L 30 min</p>	<p>5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50</p>
-----------------------------	------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------	--------------------------------------------------------------------------------------------

**Persistence/Degradability**

Not determined

**Bioaccumulation**

Not determined

**Mobility**

Chemical Name	Partition Coefficient
<p>Isopropanol 67-63-0</p>	<p>0.05</p>
<p>Ethyl acetate 141-78-6</p>	<p>0.6</p>
<p>N-Heptane 142-82-5</p>	<p>4.66</p>
<p>Toluene 108-88-3</p>	<p>2.65</p>

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
<p>Ethyl acetate 141-78-6</p>		<p>Included in waste stream: F039</p>		<p>U112</p>
<p>Toluene 108-88-3</p>	<p>U220</p>	<p>Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151</p>		<p>U220</p>

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes



## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Listed

#### Legend:

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

*EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

*ENCS - Japan Existing and New Chemical Substances*

*IECSC - China Inventory of Existing Chemical Substances*

*KECL - Korean Existing and Evaluated Chemical Substances*

*PICCS - Philippines Inventory of Chemicals and Chemical Substances*

### US Federal Regulations

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethyl acetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	67-63-0	15-25	1.0
Toluene - 108-88-3	108-88-3	<5	1.0

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3 (<5)	1000 lb	X	X	X

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental Female Reproductive

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isopropanol 67-63-0	X	X	X
Ethyl acetate 141-78-6	X	X	X

N-Heptane 142-82-5	X	X	X
Toluene 108-88-3	X	X	X

## 16. OTHER INFORMATION

**NFPA****Health Hazards**

Not determined

**Flammability**

4

**Instability**

0

**Special Hazards** Notdetermined **Personal****HMIS****Health Hazards**

Not determined

**Flammability**

Not determined

**Physical Hazards**

Not determined

**Protection** Not

determined

**Issue Date**

01-Feb-2012

**Revision Date:**

04-Oct-2017

**Revision Note**

New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**